

Taiwan Hong Chuan 48V brushless

LSW--856 (66-1M) 19.05.23

American MATE


skills requirement:

- Current limiting: $25 \pm 0.5A$, undervoltage: $39 \pm 0.5V$ (English label, label LSW856-66-1M);
- the two ends of the line, 12G folding car special shell aluminum strip. The second, third, fourth, and fifth sets of lines are the right end outgoing lines, and the first set of lines are the left end outgoing lines. The second, third, fourth, and fifth sets of lines use waterproof lines, and the outlet length includes plug-ins. (The controller is internally glued).
- LSW12G-JH-MO-181128 board
- brake mode: high level
- program number: M743Y
- with Kodis 12 magnetic steel sensor;
- with Aipuite 850C instrument (**special 5S protocol**), control power nine gear, 0 gear motor does not work.
- with Jiabo-750W motor, a speed measuring magnetic steel.
- Built-in high-level brake module (BKH-151105): module BK2 is connected to circuit board BKL, and module GND is connected to circuit board GND.
- built-in 48V headlight module (version number: Dual1-36V-48V-V1.0): the module's VB+ soldering circuit board power supply is positive, the module's GND soldering circuit board power supply is negative, the module TB is connected to the circuit board TB, module The CR is connected to the circuit board 5V.
- The brown wire of the third group is opened 200mm first and the red wire of the fifth group is opened 200mm first and then a set of 50mm red wire sleeve is sealed with heat shrinkable tube. The fifth blue line and the fifth set of green lines are respectively 200 mm and the 50 mm blue line is sealed with a heat shrinkable tube.


Number	Line num	Line col	Wire d	Function and function	Out line	fixed	Offline
One	1	red	2.0	48V power supply is positive	120	115	235
	2	black	2.0	48V power supply negative	120	120	240
two	1	blue	2.0	Motor A	600	100	700
	2	green	2.0	Motor B	600	85	685
	3	yellow	2.0	Motor C	600	70	670
	4	red	0,2	Motor Hall power supply	600	60	660
	5	black	0,2	Motor Hall power supply negative	600	60	660
	6	blue	0,2	Motor Hall Signal SA	600	60	660
	7	yellow	0,2	Motor Hall Signal SC	600	60	660
	8	green	0,2	Motor Hall Signal SB	600	60	660
	9	White	0,2	Speed signal SS	600	60	660
three	1	red	0,2	48V power supply is positive	170	65	235
	2	blue	0,2	lock	170	65	235
	3	black	0,2	48V power supply negative	170	65	235
	4	green	0,2	Communication signal TX	170	65	235
	5	yellow	0,2	Communication signal RX	170	65	235
	6	purple	0,2	Turn the power supply	170	65	235
	7	gray	0,2	Turn signal SP	170	65	235
	8	White	0,2	Brake module BKH	170	80	250
	9	Orange	0,2	Connect the fifth set of white lines	170	60	230
	10	Brown	0,2	Headlight module FL	170	80	250
four	1	red	0,2	Sensor power supply	250	45	295
	2	black	0,2	Sensor power supply negative	250	65	315
	3	White	0,2	Sensor signal TA	250	45	295
Fives	1	red	0,2	Headlight module FL	170	80	250
	2	blue	0,2	Headlight module BL	170	80	250
	3	black	0,2	48V power supply negative	170	65	235
	4	green	0,2	Headlight module BL	170	80	250
	5	yellow	0,2	Brake module BKH	170	80	250
6	White	0,2	Connect three sets of orange lines	170	60	230	



T type power head




Jun Lei 2 generation big nine core waterproof pin



Jun Lei 2 generation ten core waterproof jack



Jun Lei three core waterproof pin



Jun Lei six core waterproof jack

prepared by:	Process:	Review:	Approved:
--------------	----------	---------	-----------